

P/N MS35335-63

Description

Hole Diameter: 3/8", internal teeth, stainless steeel, MS35335 series washer

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS3533563

Minimum Qty (MOQ): 100

NSN: 5310-00-209-0790

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









^{*} See page 2 for technical characteristics

P/N MS35335-63 Specifications

Hole Diameter:	0.384 Inches Minimum And 0.398 Inches Maximum
Outside Diameter:	0.670 Inches Minimum And 0.694 Inches Maximum
Material Thickness:	0.032 Inches Minimum And 0.040 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall Or Qq-p-35,ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat External Teeth

How to Order

Order this lock washer from our inventory online by visiting https://military-fasteners.com/washers/lock+washers/MS35335-63 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.