

**Description**

Hole Diameter: 1/2", external tooth

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS3533565
Minimum Qty (MOQ):	50
NSN:	5310-00-655-6151
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS35335-65 Specifications

<b>Hole Diameter:</b>	0.513 Inches Minimum And 0.530 Inches Maximum
<b>Outside Diameter:</b>	0.880 Inches Minimum And 0.900 Inches Maximum
<b>Material Thickness:</b>	0.037 Inches Minimum And 0.045 Inches Maximum
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall Or Qq-p-35,ty 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flat External Teeth

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35335-65> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.