

Description

Hole Diameter: 1/2", external tooth

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3533565
Minimum Qty (MOQ):	50
NSN:	5310-00-655-6151
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS35335-65 Specifications

Hole Diameter:	0.513 Inches Minimum And 0.530 Inches Maximum
Outside Diameter:	0.880 Inches Minimum And 0.900 Inches Maximum
Material Thickness:	0.037 Inches Minimum And 0.045 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall Or Qq-p-35,ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat External Teeth

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35335-65> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.