

Description

Hole Diameter: 11/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS3533615 |
| Minimum Qty (MOQ): | 50 EA |
| NSN: | 5310-00-550-0286 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS35336-15 Specifications

| | |
|---|---|
| Hole Diameter: | 0.167 Inches Minimum And 0.177 Inches Maximum |
| Outside Diameter: | 0.322 Inches Nominal |
| Material Thickness: | 0.017 Inches Minimum And 0.021 Inches Maximum |
| Hardness Rating: | 40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Material: | Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1552 Overall Or Steel Comp 1053 Overall Or Steel Comp 1055 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Countersink External Teeth |
| Nondefinitive Spec/std Data: | 4 Type And 1 Style And A Grade And 1 Composition |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35336-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.