

## P/N MS35336-29

### **Description**

Hole Diameter: 17/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS3533629

Minimum Qty (MOQ): 100 EA

NSN: 5310-00-261-7163

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35336-29 Specifications

Hole Diameter:	0.255 Inches Minimum And 0.267 Inches Maximum
Outside Diameter:	0.454 Inches Nominal
Material Thickness:	0.020 Inches Minimum And 0.025 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2.or Ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Countersink External Teeth

# **How to Order**

Order this washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/lock+washers/MS35336-29">https://military-fasteners.com/washers/lock+washers/MS35336-29</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.