

Description

Hole Diameter: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS353363
Minimum Qty (MOQ):	115 EA
NSN:	5310-00-194-9206
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

# P/N MS35336-3 Specifications

Hole Diameter:	0.113 Inches Minimum And 0.123 Inches Maximum
Outside Diameter:	0.213 Inches Nominal
Material Thickness:	0.015 Inches Minimum And 0.019 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1552 Overall Or Steel Comp 1053 Overall Or Steel Comp 1055 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Countersink External Teeth
Nondefinitive Spec/std Data:	4 Type And 1 Style And A Grade And 1 Composition

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35336-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.