

Description

Hole Diameter: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS3533645 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5310-00-194-9214 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS35336-45 Specifications

| | |
|---|--|
| Hole Diameter: | 0.448 Inches Minimum And 0.463 Inches Maximum |
| Outside Diameter: | 0.867 Inches Nominal |
| Material Thickness: | 0.037 Inches Minimum And 0.045 Inches Maximum |
| Hardness Rating: | 40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Material: | Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Countersink External Teeth |
| Nondefinitive Spec/std Data: | C Type |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35336-45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.