

Description

Hole Diameter: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS353365
Minimum Qty (MOQ):	60 EA
NSN:	5310-00-579-1520
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS35336-5 Specifications

Hole Diameter:	0.113 Inches Minimum And 0.123 Inches Maximum
Outside Diameter:	0.213 Inches Nominal
Material Thickness:	0.015 Inches Minimum And 0.019 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Ty 2 Or Ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Countersink External Teeth
Nondefinitive Spec/std Data:	C Type

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35336-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.