

## P/N MS35338-137

### **Description**

Fits diameter: #8, split lock, corrosion resistant, stainless steel, MS35338 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35338137

Minimum Qty (MOQ): 100

NSN: 5310-00-933-8119

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









# P/N MS35338-137 Specifications

Hole Diameter:	0.168 Inches Minimum And 0.175 Inches Maximum
Outside Diameter:	0.296 Inches Maximum
Material Thickness:	0.040 Inches Minimum And 0.046 Inches Maximum
End Item Identification:	Mrap Rg-31/route Clearance Vehicle; Rg-33; Mrap Buffalo Mk2a2
Hardness Rating:	35.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
Material:	Steel Comp 304 Or Steel Comp 316 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams-qq-pp-35 Assn Std Single Treatment Response Overall
Style Designator:	Split Helical-right Hand
Nondefinitive Spec/std Data:	2 Style And C Class

## **How to Order**

Order this lock washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/lock+washers/MS35338-137">https://military-fasteners.com/washers/lock+washers/MS35338-137</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/lock+washers/MS35338-137">https://military-fasteners.com/washers/lock+washers/MS35338-137</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/lock+washers/MS35338-137">https://military-fasteners.com/washers/lock+washers/MS35338-137</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/msa5338-137">https://military-fasteners.com/washers/msa5338-137</a> and selecting the quantity you want <a href="https://military-fasteners.com/washers/msa5338-137">https://military-fasteners.com/washers/msa5338-137</a> and selecting the property of t