

Description

Hole Diameter: 1/4", MS35338 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3533862
Minimum Qty (MOQ):	25
NSN:	5310-00-274-8710
Schedule B:	7318.22.0000
ECCN:	9A991
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N MS35338-62 Specifications

Hole Diameter:	0.194 Inches Minimum And 0.202 Inches Maximum
Outside Diameter:	0.334 Inches Maximum
Material Thickness:	0.047 Inches Minimum And 0.053 Inches Maximum
End Item Identification:	Mrap Rg-33 And Rg-33 Auv
Hardness Rating:	45.0 Rockwell C Minimum And 53.0 Rockwell C Maximum
Material:	Steel Comp 1060 Or Steel Comp 1561 Or Steel Comp 1064 Or Steel Comp 1065 Or Steel Comp 1566 Or Steel Comp 1069 Or Steel Comp 1070 Or Steel Comp 1572 Or Steel Comp 1074 Or Steel Comp 1075 Or Steel Comp 1080 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Mil-p-16232 Ty Z Mil Spec Single Treatment Response Overall
Style Designator:	Split Helical-right Hand

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35338-62> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.