



Military-Fasteners.com

P/N MS35457-3

Description

Fastener Length: 1/2", Thread: 4-40, Head Width: 5/64", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS354573 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-579-5695 |
| Schedule B: | 8535.90.8040 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS35457-3 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.500 Inches Minimum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.178 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.109 Inches Minimum And 0.112 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.078 Inches Minimum And 0.079 Inches Maximum |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall Or Zinc Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325,ty 2,cl 3 Fed Spec 2nd Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 1936 Series |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35457-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.