



★ FASTENERS

Military-Fasteners.com

P/N MS35489-11

Description

inner diameter: 3/8" groove diameter: 5/8" groove width: 1/16", synthetic rubber grommet, hot oil and coolant resistant, MS35489 series grommet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3548911
Minimum Qty (MOQ):	25
NSN:	5325-00-291-9366
Schedule B:	4016.93.5050
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:



* See page 2 for technical characteristics

P/N MS35489-11 Specifications

Nonmetallic Hardness Rating:	45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A
Hole Diameter:	0.375 Inches Nominal
Groove Width:	0.062 Inches Nominal
Flange Thickness:	0.125 Inches Nominal
Overall Height:	0.312 Inches Nominal
Grommet Style:	Round
Large Flange Outside Diameter:	0.875 Inches Nominal
Groove Outside Diameter:	0.625 Inches Nominal
Grommet Construction Type:	Solid
Features Provided:	Coolant Resistant And Oil Resistant
Color:	Black Overall
Material:	Rubber Synthetic Overall
Material Document And Classification:	Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall
Test Data Document:	81348-mil-g-3036 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). Or 96906-ms35489-11 Standard (includes Industry Or Association Standards, Individual Manufactureer Standards, Etc.).

How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.