

P/N MS35489-118

Description

inner diameter: 5/16" groove diameter: 13/16" groove width: 1/16", synthetic rubber grommet, hot oil and coolant resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS35489118

Minimum Qty (MOQ): 20

NSN: 5325-00-834-1789

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi







^{*} See page 2 for technical characteristics

P/N MS35489-118 Specifications

| Nonmetallic Hardness Rating: | 45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A |
|---------------------------------------|----------------------------------------------------------------------------|
| Hole Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Groove Width: | 0.047 Inches Minimum And 0.079 Inches Maximum |
| Flange Thickness: | 0.125 Inches Nominal |
| Overall Height: | 0.281 Inches Minimum And 0.343 Inches Maximum |
| Grommet Style: | Round |
| Large Flange Outside Diameter: | 1.031 Inches Minimum And 1.093 Inches Maximum |
| Groove Outside Diameter: | 0.796 Inches Minimum And 0.828 Inches Maximum |
| Grommet Construction Type: | Solid |
| Features Provided: | Coolant Resistant And Oil Resistant |
| Color: | Black Overall |
| Material: | Rubber Synthetic Overall |
| Material Document And Classification: | Astm D2000 Bg515a14b24c32e036f19z Mfr Ref Single Material Response Overall |

How to Order

Order this nonmetallic grommet from our inventory online by visiting https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-118 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-118 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-118 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msas