

Description

inner diameter: 3/8" groove diameter: 1" groove width: 1/16", synthetic rubber grommet, hot oil and coolant resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------------------------|
| SKU / Model: | MS3548912 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5325-00-263-6651 |
| ECCN: | EAR99 |
| National Motor Freight: | 156600, Plastic / Rubber Article Viz: |



* See page 2 for technical characteristics

P/N MS35489-12 Specifications

| | |
|--|---|
| Nonmetallic Hardness Rating: | 45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A |
| Hole Diameter: | 0.359 Inches Minimum And 0.391 Inches Maximum |
| Groove Width: | 0.047 Inches Minimum And 0.079 Inches Maximum |
| Flange Thickness: | 0.094 Inches Nominal |
| Overall Height: | 0.234 Inches Minimum And 0.266 Inches Maximum |
| Grommet Style: | Round |
| Large Flange Outside Diameter: | 1.219 Inches Minimum And 1.281 Inches Maximum |
| Groove Outside Diameter: | 0.984 Inches Minimum And 1.016 Inches Maximum |
| Grommet Construction Type: | Solid |
| Features Provided: | Coolant Resistant And Oil Resistant |
| Color: | Black Overall |
| Material: | Rubber Synthetic Overall |
| Material Document And Classification: | Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall |

How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.