

Description

Hole Diameter: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS3548912S
Minimum Qty (MOQ):	100
NSN:	5325-00-263-6651
Schedule B:	4016.93.5050
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS35489-12S Specifications

Nonmetallic Hardness Rating:	45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A
Hole Diameter:	0.359 Inches Minimum And 0.391 Inches Maximum
Groove Width:	0.047 Inches Minimum And 0.079 Inches Maximum
Flange Thickness:	0.094 Inches Nominal
Overall Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Grommet Style:	Round
Large Flange Outside Diameter:	1.219 Inches Minimum And 1.281 Inches Maximum
Groove Outside Diameter:	0.984 Inches Minimum And 1.016 Inches Maximum
Grommet Construction Type:	Solid
Features Provided:	Coolant Resistant And Oil Resistant
Color:	Black Overall
Material:	Rubber Synthetic Overall
Material Document And Classification:	Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall

How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-12S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.