

P/N MS35489-147

Description

Hole Diameter: 3/8", MS35489 series grommet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS35489147

Minimum Qty (MOQ): 50

NSN: 5325-01-213-8434

Schedule B: 4016.93.1010

ECCN: EAR99

National Motor Freight: 156600, Plastic / Rubber Article Viz:









P/N MS35489-147 Specifications

Nonmetallic Hardness Rating:	45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A
Hole Diameter:	0.375 Inches Nominal
Groove Width:	0.094 Inches Nominal
Flange Thickness:	0.078 Inches Nominal
Overall Height:	0.219 Inches Minimum And 0.281 Inches Maximum
Grommet Style:	Round
Large Flange Outside Diameter:	0.610 Inches Minimum And 0.671 Inches Maximum
Groove Outside Diameter:	0.500 Inches Nominal
Grommet Construction Type:	Solid
Features Provided:	Coolant Resistant And Oil Resistant
Color:	Black Overall
Material:	Rubber Polyester Urethane Class Au Or Rubber Polyether Urethane Class Eu Or Rubber Butadiene-acrylonitrile Class Nbr Overall
Material Document And Classification:	Astm D2000,bg515a14b24c32e036f19z Assn Std Single Material Response Overall

How to Order

Order this nonmetallic grommet from our inventory online by visiting https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-147 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-147 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-147 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msastantary-fasteners.com/grommets/msas