

P/N MS35489-34

Description

inner diameter: 3/16", groove diameter: 5/8", groove width: 1/8", synthetic rubber, hot oil and coolant resistant, MS35489 series grommet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS3548934

Minimum Qty (MOQ): 25

NSN: 5325-00-174-9322

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









^{*} See page 2 for technical characteristics

P/N MS35489-34 Specifications

| Nonmetallic Hardness Rating: | 45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A |
|---------------------------------------|---|
| Hole Diameter: | 0.172 Inches Minimum And 0.204 Inches Maximum |
| Groove Width: | 0.109 Inches Minimum And 0.141 Inches Maximum |
| Flange Thickness: | 0.047 Inches Minimum And 0.079 Inches Maximum |
| Overall Height: | 0.219 Inches Minimum And 0.281 Inches Maximum |
| Grommet Style: | Round |
| Large Flange Outside Diameter: | 0.834 Inches Minimum And 0.906 Inches Maximum |
| Groove Outside Diameter: | 0.609 Inches Minimum And 0.641 Inches Maximum |
| Grommet Construction Type: | Solid |
| Features Provided: | Coolant Resistant And Oil Resistant |
| Color: | Black Overall |
| Material: | Rubber Synthetic Overall |
| Material Document And Classification: | Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall |

How to Order

Order this nonmetallic grommet from our inventory online by visiting https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-34 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-34 and selecting the