

Description

inner diameter: 3/16", groove diameter: 5/8", groove width: 1/8", synthetic rubber, hot oil and coolant resistant, MS35489 series grommet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3548934
Minimum Qty (MOQ):	25
NSN:	5325-00-174-9322
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N MS35489-34 Specifications

Nonmetallic Hardness Rating:	45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A
Hole Diameter:	0.172 Inches Minimum And 0.204 Inches Maximum
Groove Width:	0.109 Inches Minimum And 0.141 Inches Maximum
Flange Thickness:	0.047 Inches Minimum And 0.079 Inches Maximum
Overall Height:	0.219 Inches Minimum And 0.281 Inches Maximum
Grommet Style:	Round
Large Flange Outside Diameter:	0.834 Inches Minimum And 0.906 Inches Maximum
Groove Outside Diameter:	0.609 Inches Minimum And 0.641 Inches Maximum
Grommet Construction Type:	Solid
Features Provided:	Coolant Resistant And Oil Resistant
Color:	Black Overall
Material:	Rubber Synthetic Overall
Material Document And Classification:	Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall

How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.