

P/N MS35489-35

Military-Fasteners.com

Description

inner diameter: 1/4", groove diameter: 7/16", groove width: 1/8", synthetic rubber grommet, hot oil and coolant resistant, MS35489 series grommet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS3548935
Minimum Qty (MOQ):	25
NSN:	5325-00-185-0012
Schedule B:	4016.93.0000
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:



P/N MS35489-35 Specifications

Usla Diamatan	0.224 Jackson Minimum And 0.200 Jackson Maximum
Hole Diameter:	0.234 Inches Minimum And 0.266 Inches Maximum
Groove Width:	0.109 Inches Minimum And 0.141 Inches Maximum
Flange Thickness:	0.046 Inches Minimum And 0.078 Inches Maximum
Overall Height:	0.094 Inches Minimum And 0.156 Inches Maximum
Grommet Style:	Round
Large Flange Outside Diameter:	0.594 Inches Minimum And 0.656 Inches Maximum
Groove Outside Diameter:	0.422 Inches Minimum And 0.454 Inches Maximum
Grommet Construction Type:	Solid
Features Provided:	Coolant Resistant And Oil Resistant
Color:	Black Overall
Material:	Rubber Synthetic Overall
Material Document And Classification:	Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall

How to Order

Order this nonmetallic grommet from our inventory online by visiting <u>https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-35</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.