

## P/N MS35489-4

### **Description**

inner diameter: 3/16", groove diameter: 5/16", groove width: 1/16", synthetic rubber grommet, hot oil and coolant resistant, MS35489 series grommet

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model:	MS354894
Minimum Qty (MOQ):	50
NSN:	5325-00-174-5317
Schedule B:	4016.93.1010
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35489-4 Specifications

Nonmetallic Hardness Rating:	50.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A
Hole Diameter:	0.172 Inches Minimum And 0.204 Inches Maximum
Groove Width:	0.046 Inches Minimum And 0.078 Inches Maximum
Flange Thickness:	0.046 Inches Minimum And 0.078 Inches Maximum
Overall Height:	0.157 Inches Minimum And 0.219 Inches Maximum
Grommet Style:	Round
Large Flange Outside Diameter:	0.407 Inches Minimum And 0.469 Inches Maximum
Groove Outside Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Grommet Construction Type:	Solid
Features Provided:	Coolant Resistant And Oil Resistant
Color:	Black Overall
Material:	Rubber Synthetic Overall
Material Document And Classification:	Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall

## **How to Order**

Order this nonmetallic grommet from our inventory online by visiting <a href="https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-4">https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-4">https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-4</a> and selecting the