

**Description**

inner diameter: 1/4" groove diameter: 1" groove width: 1/16", synthetic rubber grommet, hot oil and coolant resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS354898
Minimum Qty (MOQ):	20
NSN:	5325-00-276-6087
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:



\* See page 2 for technical characteristics

## P/N MS35489-8 Specifications

<b>Nonmetallic Hardness Rating:</b>	45.0 Minimum Shore Durometer A And 55.0 Maximum Shore Durometer A
<b>Hole Diameter:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>Groove Width:</b>	0.046 Inches Minimum And 0.078 Inches Maximum
<b>Flange Thickness:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Overall Height:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>Grommet Style:</b>	Round
<b>Large Flange Outside Diameter:</b>	1.219 Inches Minimum And 1.281 Inches Maximum
<b>Groove Outside Diameter:</b>	0.984 Inches Minimum And 1.016 Inches Maximum
<b>Grommet Construction Type:</b>	Solid
<b>Features Provided:</b>	Coolant Resistant And Oil Resistant
<b>Color:</b>	Black Overall
<b>Material:</b>	Rubber Synthetic Overall
<b>Material Document And Classification:</b>	Astm D2000 Bg515a14b24c32e036f19z Assn Std Single Material Response Overall

## How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS35489-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.