

Description

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3549230
Minimum Qty (MOQ):	40 EA
NSN:	5305-00-224-0147
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	199970, Woodenware Sub6



\* See page 2 for technical characteristics

# P/N MS35492-30 Specifications

Fastener Length:	0.703 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Wood Screw (type Wd)
Countersink Angle:	80.0 Degrees Minimum And 87.0 Degrees Maximum
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall Or Zinc Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325,ty 2,cl3 Fed Spec 2nd Treatment Response Overall
Nondefinitive Spec/std Data:	1 Type And 2c Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35492-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.