

P/N MS35492-60

Description

Fastener Length: 2-1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | MS3549260 |
|-------------------------|--|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-901-3111 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts, nuts Or Screws, Noi (sub 3) |



^{*} See page 2 for technical characteristics

P/N MS35492-60 Specifications

| Fastener Length: | 2.500 Inches Nominal |
|--|---|
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.292 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.164 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Nondefinitive Spec/std Data: | 1 Type And 2c Style |

How to Order

Order this tapping screw from our inventory online by visiting https://military-fasteners.com/screws/tapping+screws/MS35492-60 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.