

Description


Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS354928
Minimum Qty (MOQ):	50
NSN:	5305-00-900-1117
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	199970, Woodenware Sub6



* See page 2 for technical characteristics

P/N MS35492-8 Specifications

Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.195 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325,ty 2,cl 3 Fed Spec 2nd Treatment Response Overall
Nondefinitive Spec/std Data:	1 Type And 2c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35492-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.