

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS354929 |
| Minimum Qty (MOQ): | 35 EA |
| NSN: | 5305-00-900-1111 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS35492-9 Specifications

| | |
|---|--|
| Fastener Length: | 0.344 Inches Minimum And 0.375 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.195 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.112 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall Or Zinc Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325,ty 2,cl 3 Fed Spec 2nd Treatment Response Overall |
| Nondefinitive Spec/std Data: | 1 Type And 2c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35492-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.