

Description

Fastener Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS3549295
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-902-4336
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS35492-95 Specifications

Fastener Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.389 Inches Minimum And 0.438 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Nonmachine Nominal Thread Diameter:	0.216 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall Or Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325,ty 2,cl 3 Fed Spec 2nd Treatment Response Overall
Nondefinitive Spec/std Data:	1 Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35492-95> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.