

## P/N MS35492-96

### **Description**

Fastener Length: 2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS3549296

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-901-2633

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35492-96 Specifications

Fastener Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.389 Inches Minimum And 0.438 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Criticality Code Justification:	Sftt
Nonmachine Nominal Thread Diameter:	0.216 Inches
Material:	Steel Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-z-325,type 2 Class 3 Fed Spec Single Treatment Response Overall Or Mil-c-81562,type 2 Class 3 Mil Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	1 Type And 2c Style

# **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35492-96">https://military-fasteners.com/screws/machine+screws/MS35492-96</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.