

P/N MS35493-77

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS3549377
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-903-5535
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	199970, Woodenware Sub6



^{*} See page 2 for technical characteristics

P/N MS35493-77 Specifications

Fastener Length:	0.828 Inches Minimum And 0.875 Inches Maximum
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.137 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall Or Zinc Overall And Chromate Overall
Surface Treatment Document And	Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325,ty 2,cl 3 Fed Spec 2nd Treatment Response
Classification:	Overall
Nondefinitive Spec/std Data:	1 Type And 1c Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35493-77 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS35493-77 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS35493-77 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms35493-77 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms35493-77 and selecting the quantity you want then cart in your cart you can check out https://military-fasteners.com/screws/ms35493-77 and selecting the your cart your ca