

P/N MS35672-1

Description

MS35672-1 Grooved Headless Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS356721

Minimum Qty (MOQ):

NSN: 5315-00-276-5742

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



P/N MS35672-1 Specifications

First End Style:	Square
Overall Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Second End Relationship With First End:	Identical
Pin Small End Diameter:	0.0459 Inches Minimum And 0.0469 Inches Maximum
Shear Strength:	300 Double Pounds Per Square Inch
First End Location:	Both Ends
Pin Large End Diameter:	0.050 Inches Minimum And 0.052 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 302b Overall Or Steel Comp 303 Overall Or Steel Uns S34723 Overall Or Steel Comp 303 Plus X Overall Or Steel Comp 303cu Overall Or Steel Comp 303f Overall Or Steel Uns S34720 Overall Or Steel Comp 303ma Overall Or Steel Comp 303pb Overall Or Steel Comp 303s Overall Or Steel Comp 303se Overall Or Steel Comp 304 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 309 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 317 Overall Or Steel Comp 317 Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 322 Overall Or Steel Comp 323 Overall Or Steel Comp 324 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall Or Steel Comp 385 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Full Length Groove

How to Order

Order this grooved headless pin from our inventory online by visiting https://military-fasteners.com/pins/grooved+headless+pins/MS35672-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.