

P/N MS35764-1202

Description

Fastener Length: 3/4", Thread: 1/4-20, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS357641202

Minimum Qty (MOQ): 40 EA

NSN: 5306-01-111-3518

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS35764-1202 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.595 Inches Minimum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Locking Feature:	Distortions Bearing Surface Of Head
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.125 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1033 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Mil-p-16232,type2,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

