

Description

Fastener Length: 1-7/32", Thread: 5/16-18, Thread Length: 27/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS357641251
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-109-6716
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35764-1251 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.835 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	1.210 Inches Minimum And 1.250 Inches Maximum
Head Style:	Distorted Head
Head Height:	0.188 Inches Minimum And 0.198 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Locking Feature:	Distortions Top Of Head
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae J429 Gr 8 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-1251> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.