

Description

Fastener Length: 1-1/2", Thread: 3/8-16, Thread Length: 63/64", MS35764 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS357641297
Minimum Qty (MOQ):	20
NSN:	5306-01-052-2402
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35764-1297 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.960 Inches Minimum And 1.438 Inches Maximum
Fastener Length:	1.460 Inches Minimum And 1.500 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.260 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
Locking Feature:	Distortions Bearing Surface Of Head
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.062 Inches Minimum And 0.500 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-1297> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.