

Description

Fastener Length: 1-45/64", Thread: 1/2-20, Thread Length: 1-37/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS357641436
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-020-9565
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS35764-1436 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.565 Inches Minimum
Fastener Length:	1.690 Inches Minimum And 1.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	0.798 Inches Minimum And 0.812 Inches Maximum
Locking Feature:	Distortions Bearing Surface Of Head
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.125 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Phosphate Overall
Surface Treatment Document And Classification:	Mil-p-16232,ty Z,cI 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-1436> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.