

Description

Fastener Length: 3", Thread: 1/2-20, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS357641445
Minimum Qty (MOQ):	25
NSN:	5305-01-496-6745
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35764-1445 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Nominal
Fastener Length:	3.000 Inches Nominal
Head Style:	Distorted Head
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	0.798 Inches Minimum And 0.812 Inches Maximum
Locking Feature:	Distortions Head
End Item Identification:	2350014186654
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-1445> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.