

**Description**

Fastener Length: 1-1/4", Thread: 5/8-18, Thread Length: 1-1/4", MS35764 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS357641545                               |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5306-01-132-3363                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS35764-1545 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 2a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 1.079 Inches Minimum And 1.250 Inches Maximum   |
| <b>Fastener Length:</b>                               | 1.190 Inches Minimum And 1.250 Inches Maximum   |
| <b>Head Style:</b>                                    | Distorted Head  |
| <b>Head Height:</b>                                   | 0.375 Inches Minimum And 0.390 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.983 Inches Minimum And 1.000 Inches Maximum   |
| <b>Locking Feature:</b>                               | Distortions Top Of Head   |
| <b>Nominal Thread Diameter:</b>                       | 0.625 Inches  |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 18  |
| <b>Minimum Tensile Strength:</b>                      | 150000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall   |
| <b>Material:</b>                                      | Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1033 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-1545> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.