



Military-Fasteners.com

P/N MS35764-1619

Description

Fastener Length: 3-3/4", Thread: 3/4-16, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS357641619
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-280-5525
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35764-1619 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Nominal
Fastener Length:	3.650 Inches Minimum And 3.750 Inches Maximum
Head Style:	Distorted Head
Head Height:	0.438 Inches Minimum And 0.458 Inches Maximum
Width Between Flats:	1.106 Inches Minimum And 1.125 Inches Maximum
Locking Feature:	Distortions Head
Nominal Thread Diameter:	0.750 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	J429 Grade 8 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-1619> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.