

Description

Fastener Length: 1-63/64", Thread: 3/8-16, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35764238 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-01-083-4082 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS35764-238 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.960 Inches Minimum And 1.438 Inches Maximum |
| Fastener Length: | 1.960 Inches Minimum And 2.000 Inches Maximum |
| Head Style: | Distorted Head |
| Head Height: | 0.250 Inches Minimum And 0.260 Inches Maximum |
| Width Between Flats: | 0.551 Inches Minimum And 0.562 Inches Maximum |
| Locking Feature: | Distortions Top Of Head |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.562 Inches Minimum And 1.000 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Assn Std All Material Responses Overall |
| Surface Treatment: | Phosphate Zinc Overall |
| Surface Treatment Document And Classification: | Mil-p-16232,ty Z Cl 2 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-238> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.