



Military-Fasteners.com

P/N MS35764-258

## Description

Fastener Length: 3-1/4", Thread: 7/16-14, Thread Length: 1-37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS35764258
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-097-8204
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS35764-258 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.045 Inches Minimum And 1.589 Inches Maximum
Fastener Length:	3.170 Inches Minimum And 3.250 Inches Maximum
Head Style:	Distorted Head
Head Height:	0.281 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
Locking Feature:	Distortions Top Of Head
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.661 Inches Minimum And 2.125 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1033 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall
Material Document And Classification:	Sae Assn Std All Material Responses Overall
Surface Treatment:	Phosphate Zinc Overall
Surface Treatment Document And Classification:	Mil-p-16232 Ty 2 Cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-258> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.