

**Description**

Fastener Length: 3-59/64", Thread: 7/16-14, Thread Length: 1-3/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35764261
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-083-6442
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS35764-261 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.045 Inches Minimum And 1.589 Inches Maximum
<b>Fastener Length:</b>	3.920 Inches Minimum And 4.000 Inches Maximum
<b>Head Style:</b>	Distorted Head
<b>Head Height:</b>	0.281 Inches Minimum And 0.291 Inches Maximum
<b>Width Between Flats:</b>	0.612 Inches Minimum And 0.625 Inches Maximum
<b>Locking Feature:</b>	Distortions Top Of Head
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	2.411 Inches Minimum And 2.875 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	14
<b>Minimum Tensile Strength:</b>	150000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Phosphate Zinc Overall
<b>Surface Treatment Document And Classification:</b>	Mil-p-16232 Tyz Cl2 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-261> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.