

Description

Fastener Length: 3-59/64", Thread: 7/16-14, Thread Length: 1-3/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35764261
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-083-6442
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS35764-261 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.045 Inches Minimum And 1.589 Inches Maximum
Fastener Length:	3.920 Inches Minimum And 4.000 Inches Maximum
Head Style:	Distorted Head
Head Height:	0.281 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
Locking Feature:	Distortions Top Of Head
Nominal Thread Diameter:	0.438 Inches
Grip Length:	2.411 Inches Minimum And 2.875 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae Assn Std All Material Responses Overall
Surface Treatment:	Phosphate Zinc Overall
Surface Treatment Document And Classification:	Mil-p-16232 Tyz Cl2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-261> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.