



Military-Fasteners.com

P/N MS35764-850

Description

Fastener Length: 1-1/4", Thread: 7/16-14, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35764850 |
| Minimum Qty (MOQ): | 255 EA |
| NSN: | 5306-01-253-1612 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS35764-850 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.065 Inches Minimum And 1.125 Inches Maximum |
| Fastener Length: | 1.190 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Distorted Head |
| Head Height: | 0.281 Inches Minimum And 0.291 Inches Maximum |
| Width Between Flats: | 0.612 Inches Minimum And 0.625 Inches Maximum |
| Locking Feature: | Distortions Bearing Surface Of Head |
| Nominal Thread Diameter: | 0.438 Inches |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 14 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Grade 8 Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35764-850> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.