

P/N MS35769-13

Military-Fasteners.com

Description

inner diameter: 11/16", thickness 3/32", copper

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS3576913
Minimum Qty (MOQ):	20
NSN:	5330-01-352-3362
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N MS35769-13 Specifications

Cross-sectional Shape Style:	Metal With Soft Filler
Temp Rating:	500.0 Deg Fahrenheit
Outside Diameter:	0.922 Inches Minimum And 0.953 Inches Maximum
Aperture Diameter:	0.688 Inches Minimum And 0.703 Inches Maximum
Cross-sectional Thickness:	0.078 Inches Minimum And 0.109 Inches Maximum
Criticality Code Justification:	Matt
Maximum Pressure Rating:	200.0 Pounds Per Square Inch
Environmental Attribute Code:	Asbestos Alternative Products
Special Features:	As Differentiated By Filler Of Non-asbestos Material
Material:	Copper Case
Material:	Fiber Nonasbestos Core And Asphalt Core And Rubber Butadiene-acrylonitrile Class Nbr Core
Material Document And Classification:	Hh-g-101 Fed Spec Single Material Response Case
Material Document And Classification:	Hh-g-101,type 3 Fed Spec Single Material Response Core
Style Designator:	Circular

How to Order

Order this gasket from our inventory online by visiting <u>https://military-fasteners.com/gaskets/gaskets/MS35769-13</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.