

Description

inner diameter: 1-3/4", thickness 3/32", gasket

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3576948
Minimum Qty (MOQ):	10
NSN:	5330-01-354-6626
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N MS35769-48 Specifications

Cross-sectional Shape Style:	Metal With Soft Filler
Temp Rating:	500.0 Deg Fahrenheit
Outside Diameter:	1.984 Inches Minimum And 2.000 Inches Maximum
Aperture Diameter:	1.750 Inches Minimum And 1.766 Inches Maximum
Cross-sectional Thickness:	0.079 Inches Minimum And 0.109 Inches Maximum
Criticality Code Justification:	Matt
Maximum Pressure Rating:	200.0 Pounds Per Square Inch
Environmental Attribute Code:	Asbestos Alternative Products
Special Features:	As Differentiated By Filler Of Non-asbestos Material
Material:	Copper Case
Material:	Fiber Nonasbestos Core And Asphalt Core And Rubber Butadiene-acrylonitrile Class Nbr Core
Material Document And Classification:	Hh-g-101 Fed Spec Single Material Response Case
Material Document And Classification:	Hh-g-101,type 3 Fed Spec All Material Responses Core
Style Designator:	Circular

How to Order

Order this gasket from our inventory online by visiting <https://military-fasteners.com/gaskets/gaskets/MS35769-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.