

P/N MS35769-9

Description

inner diameter: 1/2", thickness 3/32", MS35769 series gasket

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS357699

Minimum Qty (MOQ): 20

NSN: 5330-01-355-3686

Schedule B: 7415.21.0000

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



^{*} See page 2 for technical characteristics

P/N MS35769-9 Specifications

Cross-sectional Shape Style:	Metal With Soft Filler
Outside Diameter:	0.734 Inches Minimum And 0.750 Inches Maximum
Aperture Diameter:	0.500 Inches Minimum And 0.516 Inches Maximum
Cross-sectional Thickness:	0.078 Inches Minimum And 0.110 Inches Maximum
Criticality Code Justification:	Matt
Maximum Pressure Rating:	200.0 Pounds Per Square Inch
Environmental Attribute Code:	Asbestos Alternative Products
Special Features:	As Differentiated By Filler Of Non-asbestos Material
Material:	Copper Case
Material:	Fiber Nonasbestos Core And Asphalt Core And Rubber Butadiene-acrylonitrile Class Nbr Core
Material Document And Classification:	Hh-g-101 Fed Spec Single Material Response Case
Material Document And Classification:	Hh-g-101,type 3 Fed Spec All Material Responses Core
Style Designator:	Circular

How to Order

Order this gasket from our inventory online by visiting https://military-fasteners.com/gaskets/gaskets/MS35769-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/gaskets/MS35769-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/gaskets/MS35769-9 and selecting the quantity you want then click "add to cart".