

Description

Fastener Length: 3/16", Thread: 2-56, Head Width: 1/32", Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS510172
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-253-4871
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51017-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Maximum
Fastener Length:	0.188 Inches Nominal
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Square
Nominal Thread Diameter:	0.086 Inches
Width Across Flats:	0.035 Inches Minimum And 0.036 Inches Maximum
Thread Quantity Per Inch:	56
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec 1st Treatment Response Overall And Qq-z-325,type 2,class 3 Fed Spec 2nd Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 4 Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51017-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.