

Description

Fastener Length: 3/16", Thread: 0-80, Head Width: ", Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS510232
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-990-0379
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51023-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.060 Inches
Width Across Flats:	0.028 Inches Nominal
Thread Quantity Per Inch:	80
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 302b Overall Or Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 309s Overall Or Steel Comp 310 Overall Or Steel Comp 310s Overall Or Steel Comp 314 Overall Or Steel Comp 316 Overall Or Steel Comp 316l Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall Or Steel Comp 384 Overall Or Steel Comp 385 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 4 Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51023-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.