

Description

Fastener Length: 3/8", Thread: 1/2-20, Head Width: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5102393
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-532-4398
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51023-93 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Point Length:</b>	0.049 Inches Minimum And 0.054 Inches Maximum
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>End Item Identification:</b>	Mk25
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.250 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Point Chamfer Angle:</b>	40.0 Degrees Minimum And 50.0 Degrees Maximum
<b>Material:</b>	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 314 Overall Or Steel Comp 316 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51023-93> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.