

P/N MS51029-26

Description

Fastener Length: 3/16", Thread: 8-32, Head Width: 1/16", Thread Length: 3/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS5102926

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-757-6311

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS51029-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.078 Inches Nominal
Thread Quantity Per Inch:	32
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 303f Overall Or Steel Comp 304 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 316 Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 323 Overall Or Steel Comp 324 Overall Or Steel Comp 348 Overall Or Steel Comp 385 Overall Or Steel Comp 384 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51029-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.