

**Description**

Fastener Length: 5/8", Thread: 1/2-20, Head Width: 1/4", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS51031149
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-611-7113
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS51031-149 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.625 Inches Nominal
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Locking Feature:</b>	Patch Or Pellet Or Strip Threads
<b>Point Diameter:</b>	0.270 Inches Minimum And 0.291 Inches Maximum
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>End Item Identification:</b>	Nsn 2350-01-509-3953
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.250 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 National Std/spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51031-149> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.