

**Description**

Fastener Length: 1/8", Thread: 2-56, Head Width: 3/64", Thread Length: 3/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS510451
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-182-9401
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS51045-1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.089 Inches Minimum And 0.115 Inches Maximum
<b>Fastener Length:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Half Dog
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Width Across Flats:</b>	0.035 Inches Nominal
<b>Thread Quantity Per Inch:</b>	56
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Type And 6 Style

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51045-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.